


Model: XLC200W



General Data

Lamp Type	Lumileds
Lamp No.	3030 2D
Lamp Watts	200 W
Lamp Lumens	26000lm
Lamp Life	50000 hrs
CRI	>80 Ra
IP Rating	IP 65
Weight (Kgs)	7.55kg
Input Voltage	AC100-277V
Dimming	1-10 W / DALI
Color Temperature	3000K/4000K
Operation Temperature	-40 to +50




Construction Data

IP rating	65 waterproof
Housing	AL6063 Aluminium
Protection finishing	Powder-coated black colour finish
Glass	Tempered glass diffuser
Loading capacity	/
Cable Gland	IP65
Gasket	Silicone rubber gasket

Electrical Data

Input voltage	AC100-277V
Cable	Cable gland for waterproof IP65

Photometric Data



APPLICATIONS

Suitable for Warehouses, Workshops, Gymnasiums, Gas Stations, Toll Stations. Supermarkets, Exhibition halls and many other Industrial and commercial lighting purposes


PRODUCT DESCRIPTION

LED Hilux Linear light, 5 years warranty, Lumileds LED, High quality aluminum body with Stainless steel screws, corrosion resistance. Available in multiple dimming options such as Dali and 1-10V Dimming.

FIXTURE CONSTRUCTION

3030 2D Lumileds LED with AL6063 Powder-coated black colour finish Aluminium Body and empered glass diffuser

Dimension Drawing



Accessories



Angle Bracket



Radar Sensor

Lamp Options

Part Number	CCT	Beam angle
XLC200W330X70	3000 K	30x70°
XLC200W430X70	4000 K	30x70°
XLC200W530X70	5000 K	30x70°
XLC200W5730X70	5700 K	30x70°
XLC200W360X100	3000 K	60x100°
XLC200W460X100	4000 K	60x100°
XLC200W560X100	5000 K	60x100°
XLC200W5760X100	5700 K	60x100°
XLC200W3120	3000 K	120°
XLC200W4120	4000 K	120°
XLC200W5120	5000 K	120°
XLC200W57120	5700 K	120°