

Model: OLFA4060



General Data

Model Number	OLFA4060600W	OLFA3060700W
Power	600W	700W
LED type	CREE LED	
Luminous flux	85lm/w	
CCT	3000K,4000K,RGBW as standard. Different CCT upon request.	
CRI	80+	
Beam angle	10°,20°,30°,45°,60°	
Dimension	400 x 600 x 140mm	
Lamp Life	50000 hrs	
SDCM	≤5	
Ambient Temp.	-30°C~+35°C	
Oper. Temp.	-15~50°C	
Certifications	CE, RoHS	

Electrical Data

Input voltage	AC85-265V 50-60Hz
Cable	300mm 2pins 1.5mm ² rubber cable

Accessories

Shield	Anti-glare shield
--------	-------------------

APPLICATIONS

These luminaires are designed using weatherproof and non-corrosive materials, widely used in exterior applications, such as lighting architectural features, parks, footpaths etc.

PRODUCT DESCRIPTION

Projector luminaire for outdoor installation, aluminium body, Glass diffuser, stainless steel screws, available with the flexibility for landscape installation. Low power LED, IP65 rating.


FIXTURE CONSTRUCTION

Die-casting aluminum body and composite metal high efficiency heat dissipation patent technology for better cooling performance,with Die-casting Aluminium for housing,tempered. Silicone gasket and cable gland for waterproof IP65


Construction Data

IP rating	IP66 Waterproof
IK rating	IK06
Housing	Die-casting Aluminium
Finishing	Powder coated painting in black color
Trim	Die-casting Aluminium
Glass	Ultra clear tempered glass
Bracket	Standard 304 stainless steel damping rotating bracket with locking function
Cable Gland	PG7 IP67
Gasket	PMQ silicone gasket seal

Dimension Drawing



Photometric Data



OLFA4060600W 600w options

Part Number	CCT	Beam angle
OLFA4060600WC3B10	3000 K	10°
OLFA4060600WC4B10	4000 K	10°
OLFA4060600WCRGBWB10	RGBW	10°
OLFA4060600WC3B20	3000 K	20°
OLFA4060600WC4B20	4000 K	20°
OLFA4060600WCRGBWB20	RGBW	20°
OLFA4060600WC3B30	3000 K	30°
OLFA4060600WC4B30	4000 K	30°
OLFA4060600WCRGBWB30	RGBW	30°
OLFA4060600WC3B45	3000 K	45°
OLFA4060600WC4B45	4000 K	45°
OLFA4060600WCRGBWB45	RGBW	45°
OLFA4060600WC3B60	3000 K	60°
OLFA4060600WC4B60	4000 K	60°
OLFA4060600WCRGBWB36	RGBW	60°

OLFA4060700W 700w options

Part Number	CCT	Beam angle
OLFA4060700WC3B10	3000 K	10°
OLFA4060700WC4B10	4000 K	10°
OLFA4060700WCRGBWB10	RGBW	10°
OLFA4060700WC3B20	3000 K	20°
OLFA4060700WC4B20	4000 K	20°
OLFA4060700WCRGBWB20	RGBW	20°
OLFA4060700WC3B30	3000 K	30°
OLFA4060700WC4B30	4000 K	30°
OLFA4060700WCRGBWB30	RGBW	30°
OLFA4060700WC3B45	3000 K	45°
OLFA4060700WC4B45	4000 K	45°
OLFA4060700WCRGBWB45	RGBW	45°
OLFA4060700WC3B60	3000 K	60°
OLFA4060700WC4B60	4000 K	60°
OLFA4060700WCRGBWB36	RGBW	60°