
XL marlin Lighting

Decorative Window lights (OLWIN3001D) Installation Instruction

The user: thank you for your purchase use this product, read this instruction manual before usage

Model: OLWIN3001D
Rated Voltage: DC24V
Rated Power: 5W
IP Grade: IP66

5. Insulation protection level: Class III6.Operating Temperature: 15~50°C







- Always disconnect the power supply before installing or performing any maintenance operations.
- Installation should be carried out by a suitably qualified person in accordance with good electrical practice and the appropriate national wiring regulations.
- These luminaires are widely used in commercial lighting, home decoration lighting, art gallery and museums.
- Only can be touched after 3 minutes later when power off, so as to avoid burns.
- Dismantling and refit are forbidden
- Installation on inflammables is forbidden.

If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.

- 1. Select a suitable location for your window light. This window light can be installed on the base of the windowsill, surface mounted on the wall side of the windowsill, or fixed on the ceiling of the windowsill. It can also be used as gallery light which can be installed on the wall, ground or ceiling when it's indoor, and it can be installed on the wall and ceiling when it's outdoor.
- 2. Fix the fixture with the provided two screws.





2. Connect the electric supply wires of "L", "N", "Ground" to the corresponding "L", "N", "Ground" of the fixture's wires with the waterproof connector IP65 at least in parallel circuit if it's outdoor application.



indicate same protection class IP 65 junction box .



5. Ensure everything is installed very well, and then turn on the power for the application.

