


Model: SL24V21.6IP68



General Data

System Watts	21.6W
Voltage	24V
LED Distance	0.83 cm
Roll Length	5m
Max to connect	1 Rolls
Cutting Distance	4.9 cm
PCB Colour	White
Lumen lm p/m	2640lm
Beam angle	120°
LED Type	5050
LED Qty p/m	120
Connection Type	Stripped wire
IP Rating	IP68

Dimension Drawing



APPLICATIONS

Ideal for highlighting cove lights, wall back light, mirror back light, and staircase lighting for retail, commercial and domestic applications.

PRODUCT DESCRIPTION

LED Strip light made of LED chips, 120 deg beam angle, very slim depth and width, comes in 5 meters roll, with 3M adhesive tape. IP68

FIXTURE CONSTRUCTION

Easy installation and removal can be connected though stripped wires, made of printed circuit and silicon covers to IP68. with 3M adhesive tape.

Strip light options

Color	Part Number	CCT
	SL24V21.6IP68RGB	Red Green Blue
	SL24V21.6IP68RGBW	Red Green Blue White
	SL24V21.6IP68CW	Cool White Warm White

- Driver to be order separately
- Cable distance should be taken into consideration.

Driver: Constant Voltage Output

Driver Code	Watt	IP rate	Meter	Warranty
SRP-2108-24-200W	100 W	IP 20	1 - 8 Meter Max	5 years