

**Model: OLFA060**



**General Data**

<b>Model Number</b>	OLFA0606W	OLFA0609W	OLFA06012W
<b>Power</b>	6W	9W	12W
<b>LED type</b>	CREE LED		
<b>Luminous flux</b>	85lm/w		
<b>CCT</b>	3000K, 4000K.as standard. Different CCT upon request.		
<b>CRI</b>	80+		
<b>Beam angle</b>	15°,20°,30°,45°, 60°		
<b>Dimension</b>	60x60x69mm		
<b>Lamp Life</b>	50000 hrs		
<b>SDCM</b>	≤5		
<b>Ambient Temp.</b>	-30°C~+35°C		
<b>Oper. Temp.</b>	-15~50°C		
<b>Certifications</b>	CE, RoHS		

**Construction Data**

<b>IP rating</b>	IP66 Waterproof
<b>IK rating</b>	IK06
<b>Housing</b>	Die-casting Aluminium
<b>Finishing</b>	Powder coated painting in black color
<b>Trim</b>	Die-casting Aluminium
<b>Glass</b>	Ultra clear temperedglass
<b>Bracket</b>	Standard 304 stainless steel damping rotating bracket with locking function
<b>Cable Gland</b>	PG7 IP67
<b>Gasket</b>	PMQ silicone gasket seal

**Electrical Data**




<b>Input voltage</b>	DC24V
<b>Cable</b>	300mm 2pins 1.5mm <sup>2</sup> rubber cable

**Accessories**

<b>Shield</b>	Anti-glare shield
---------------	-------------------

**Dimension Drawing**

**Photometric Data**



**APPLICATIONS**

These luminaires are designed using weatherproof and non-corrosive materials, widely used in exterior applications, such as lighting architectural features, parks, footpaths etc.

**PRODUCT DESCRIPTION**

Projector luminaire for outdoor installation, aluminium body, Glass diffuser, stainless steel screws, available with the flexibility for landscape installation. Low power LED, IP65 rating.

**FIXTURE CONSTRUCTION**

Die-casting aluminum lamp body and composite metal high efficiency heat dissipation patent technology for better cooling performance,with Die-casting Aluminium for housing,tempered. Silicone gasket and cable gland for waterproof IP65

**OLFA0606W 6W OPTIONS**

Part Number	CCT	Beam angle
<b>OLFA0606WC3B15</b>	3000 K	15°
<b>OLFA0606WC4B15</b>	4000 K	15°
<b>OLFA0606WC3B20</b>	3000 K	20°
<b>OLFA0606WC4B20</b>	4000 K	20°
<b>OLFA0606WC3B30</b>	3000 K	30°
<b>OLFA0606WC4B30</b>	4000 K	30°
<b>OLFA0606WC3B45</b>	3000 K	45°
<b>OLFA0606WC4B45</b>	4000 K	45°
<b>OLFA0606WC3B60</b>	3000 K	60°
<b>OLFA0606WC4B60</b>	4000 K	60°

**OLFA0609W 9W OPTIONS**

Part Number	CCT	Beam angle
<b>OLFA0609WC3B15</b>	3000 K	15°
<b>OLFA0609WC4B15</b>	4000 K	15°
<b>OLFA0609WC3B20</b>	3000 K	20°
<b>OLFA0609WC4B20</b>	4000 K	20°
<b>OLFA0609WC3B30</b>	3000 K	30°
<b>OLFA0609WC4B30</b>	4000 K	30°
<b>OLFA0609WC3B45</b>	3000 K	45°
<b>OLFA0609WC4B45</b>	4000 K	45°
<b>OLFA0609WC3B60</b>	3000 K	60°
<b>OLFA0609WC4B60</b>	4000 K	60°

**OLFA06012W 12W OPTIONS**

Part Number	CCT	Beam angle
<b>OLFA06012WC3B15</b>	3000 K	15°
<b>OLFA06012WC4B15</b>	4000 K	15°
<b>OLFA06012WC3B20</b>	3000 K	20°
<b>OLFA06012WC4B20</b>	4000 K	20°
<b>OLFA06012WC3B30</b>	3000 K	30°
<b>OLFA06012WC4B30</b>	4000 K	30°
<b>OLFA06012WC3B45</b>	3000 K	45°
<b>OLFA06012WC4B45</b>	4000 K	45°
<b>OLFA06012WC3B60</b>	3000 K	60°
<b>OLFA06012WC4B60</b>	4000 K	60°