

Model: OLFA400



General Data

Model Number	OLFA400400W	OLFA400450W
Power	400W	450W
LED type	CREE LED	
Luminous flux	85lm/w	
CCT	3000K,4000K,RGBW as standard. Different CCT upon request.	
CRI	80+	
Beam angle	10°,20°,30°,45°,60°	
Dimension	400 x 400 x 295mm	
Lamp Life	50000 hrs	
SDCM	≤5	
Ambient Temp.	-30°C~+35°C	
Oper. Temp.	-15~50°C	
Certifications	CE, RoHS	

Electrical Data

Input voltage	AC85-265V 50-60Hz
Cable	300mm 2pins 1.5mm² rubber cable

Accessories

Spike	Code SPK
--------------	----------

If Visor is required add VZR at the end of the part No.

OLFA400400W 400w options

Part Number	CCT	Beam angle
OLFA400400WC3B10	3000 K	10°
OLFA400400WC4B10	4000 K	10°
OLFA400400WCRGBWB10	RGBW	10°
OLFA400400WC3B20	3000 K	20°
OLFA400400WC4B20	4000 K	20°
OLFA400400WCRGBWB20	RGBW	20°
OLFA400400WC3B30	3000 K	30°
OLFA400400WC4B30	4000 K	30°
OLFA400400WCRGBWB30	RGBW	30°
OLFA400400WC3B45	3000 K	45°
OLFA400400WC4B45	4000 K	45°
OLFA400400WCRGBWB45	RGBW	45°
OLFA400400WC3B60	3000 K	60°
OLFA400400WC4B60	4000 K	60°
OLFA400400WCRGBWB36	RGBW	60°

OLFA400450W 450w options

Part Number	CCT	Beam angle
OLFA400450WC3B10	3000 K	10°
OLFA400450WC4B10	4000 K	10°
OLFA400450WCRGBWB10	RGBW	10°
OLFA400450WC3B20	3000 K	20°
OLFA400450WC4B20	4000 K	20°
OLFA400450WCRGBWB20	RGBW	20°
OLFA400450WC3B30	3000 K	30°
OLFA400450WC4B30	4000 K	30°
OLFA400450WCRGBWB30	RGBW	30°
OLFA400450WC3B45	3000 K	45°
OLFA400450WC4B45	4000 K	45°
OLFA400450WCRGBWB45	RGBW	45°
OLFA400450WC3B60	3000 K	60°
OLFA400450WC4B60	4000 K	60°
OLFA400450WCRGBWB36	RGBW	60°

APPLICATIONS

These luminaires are designed using weatherproof and non-corrosive materials, widely used in exterior applications, such as lighting architectural features, parks, footpaths etc.

PRODUCT DESCRIPTION

Projector luminaire for outdoor installation, aluminium body, Glass diffuser, stainless steel screws, available with the flexibility for landscape installation. Low power LED, IP65 rating.


FIXTURE CONSTRUCTION

Die-casting aluminum body and composite metal high efficiency heat dissipation patent technology for better cooling performance,with Die-casting Aluminium for housing,tempered. Silicone gasket and cable gland for waterproof IP65

Construction Data

IP rating	IP66 Waterproof
IK rating	IK06
Housing	Die-casting Aluminium
Finishing	Powder coated painting in black color
Trim	Die-casting Aluminium
Glass	Ultra clear tempered glass
Bracket	Standard 304 stainless steel damping rotating bracket with locking function
Cable Gland	PG7 IP67
Gasket	PMQ silicone gasket seal

Dimension Drawing



Photometric Data

