

**Model: OLMC170**



**General Data**

Model Number	OLMC17054W	OLMC17072W
Power	54W	72W
LED type	CREE LED	
Luminous flux	85lm/w	
CCT	3000K, 4000K as standard. Different CCT upon request.	
CRI	80+	
Beam angle	8°, 10°, 20°, 30°, 45°, 60°	
Dimension	Ø170x168mm	
Lamp Life	50000 hrs	
SDCM	≤3	
Ambient Temp.	-30°C~+35°C	
Oper. Temp.	-15~50°C	
Certifications	CE, RoHS	

**Electrical Data**

Input voltage	AC85-265V 50-60Hz
Cable	300mm 2pins 1.5mm² rubber cable

**Accessories**

Shield	Anti-glare shield
--------	-------------------

**APPLICATIONS**

These luminaires are designed using weatherproof and non-corrosive materials, widely used in exterior applications, such as lighting architectural features, parks, footpaths etc.

**PRODUCT DESCRIPTION**

Projector luminaire for outdoor installation, aluminium body, Glass diffuser, stainless steel screws, available with the flexibility for landscape installation. Low power LED, IP65 rating.


**FIXTURE CONSTRUCTION**

Die-casting aluminum body and composite metal high efficiency heat dissipation patent technology for better cooling performance, with Die-casting Aluminium for housing, tempered. Silicone gasket and cable gland for waterproof IP65


**Construction Data**

IP rating	IP66 Waterproof
IK rating	IK06
Housing	Die-casting Aluminium
Finishing	Powder coated painting in black color
Trim	Die-casting Aluminium
Glass	Ultra clear tempered glass
Bracket	Standard 304 stainless steel damping rotating bracket with locking function
Cable Gland	PG7 IP67
Gasket	PMQ silicone gasket seal

**Dimension Drawing**



**Photometric Data**



**OLMC17054W 54w options**

Part Number	CCT	Beam angle
OLMC17054WC3B10	3000 K	10°
OLMC17054WC4B10	4000 K	10°
OLMC17054WCRGBWB10	RGBW	10°
OLMC17054WC3B20	3000 K	20°
OLMC17054WC4B20	4000 K	20°
OLMC17054WCRGBWB20	RGBW	20°
OLMC17054WC3B30	3000 K	30°
OLMC17054WC4B30	4000 K	30°
OLMC17054WCRGBWB30	RGBW	30°
OLMC17054WC3B45	3000 K	45°
OLMC17054WC4B45	4000 K	45°
OLMC17054WCRGBWB45	RGBW	45°
OLMC17054WC3B60	3000 K	60°
OLMC17054WC4B60	4000 K	60°
OLMC17054WCRGBWB36	RGBW	60°

**OLMC17072W 72w options**

Part Number	CCT	Beam angle
OLMC17072WC3B10	3000 K	10°
OLMC17072WC4B10	4000 K	10°
OLMC17072WCRGBWB10	RGBW	10°
OLMC17072WC3B20	3000 K	20°
OLMC17072WC4B20	4000 K	20°
OLMC17072WCRGBWB20	RGBW	20°
OLMC17072WC3B30	3000 K	30°
OLMC17072WC4B30	4000 K	30°
OLMC17072WCRGBWB30	RGBW	30°
OLMC17072WC3B45	3000 K	45°
OLMC17072WC4B45	4000 K	45°
OLMC17072WCRGBWB45	RGBW	45°
OLMC17072WC3B60	3000 K	60°
OLMC17072WC4B60	4000 K	60°
OLMC17072WCRGBWB36	RGBW	60°