


Model: PR4S12IP20WH



General Data

Power	12W
LED type	LED COB
Luminous flux	1188/1250 lm
CCT	3000K or 4000K as standard. Different CCT upon request.
CRI	>83 Ra
Beam angle	40°
Dimension	Ø100x45 mm
Cut out dia.	Ø90 mm
Weight (kgs)	0.95 Kgs
Lamp Life	50000 hrs
SDCM	≤5
Oper. Temp.	C -10°-45°
Certifications	CE, RoHS
Trim Color	White
Dimming	1-10V/DALI

Construction Data

IP rating	20 Indoor
Housing	Solid aluminum housing CNC machined body
Protection finishing	passivated (anodizing) anti-corrosion finishing
Glass	/
Loading capacity	/
Cable Gland	IP20
Gasket	Silicone rubber gasket

Electrical Data

Input voltage	AC 230~240V
Cable	Cable gland

Accessories

Mounted Accessory	/
Clip	/

APPLICATIONS

Ideal for general lighting in retail, commercial and domestic applications. Particularly suitable where glare can be an issue because this light fixture has very low glare index


PRODUCT DESCRIPTION

Prolux down light is brilliant down light for general lighting, and wet areas made of die cast aluminum body, trim and heat sink, specular reflector to control the glare temperature, and high CRI 83 Ra. dimming is on request. IP20

FIXTURE CONSTRUCTION

Easy installation using screw arrangement for fixing from below, Using a reflector and single Citizen COB type LED this slim down light produces a very wide spill light and a nice 40 wide degree beamr, the robust construction which is made from die cast aluminum and electronic remote driver.

Dimension Drawing




Lamp Options

Part Number	CCT	Beam angle
PR4S12IP20WH3	3000 K	40°
PR4S12IP20WH4	4000 K	40°

Photometric Data

Light Distribution Curve [Unit: cd]



Lux distance Curve

