

Model: OLFA3040



General Data

Model Number	OLFA3040300W	OLFA3040350W
Power	300W	350W
LED type	CREE LED	
Luminous flux	85lm/w	
CCT	3000K,4000K,RGBW as standard. Different CCT upon request.	
CRI	80+	
Beam angle	10°,20°,30°,45°,60°	
Dimension	300 x 400 x 245mm	
Lamp Life	50000 hrs	
SDCM	≤5	
Ambient Temp.	-30°C~+35°C	
Oper. Temp.	-15~50°C	
Certifications	CE, RoHS	

Electrical Data

Input voltage	AC85-265V 50-60Hz
Cable	300mm 2pins 1.5mm² rubber cable

Accessories

Shield	Anti-glare shield
---------------	-------------------

APPLICATIONS

These luminaires are designed using weatherproof and non-corrosive materials, widely used in exterior applications, such as lighting architectural features, parks, footpaths etc.

PRODUCT DESCRIPTION

Projector luminaire for outdoor installation, aluminium body, Glass diffuser, stainless steel screws, available with the flexibility for landscape installation. Low power LED, IP65 rating.



FIXTURE CONSTRUCTION

Die-casting aluminum body and composite metal high efficiency heat dissipation patent technology for better cooling performance,with Die-casting Aluminium for housing,tempered. Silicone gasket and cable gland for waterproof IP65


Construction Data

IP rating	IP66 Waterproof
IK rating	IK06
Housing	Die-casting Aluminium
Finishing	Powder coated painting in black color
Trim	Die-casting Aluminium
Glass	Ultra clear tempered glass
Bracket	Standard 304 stainless steel damping rotating bracket with locking function
Cable Gland	PG7 IP67
Gasket	PMQ silicone gasket seal

Dimension Drawing



Photometric Data



OLFA3040300W 300w options

Part Number	CCT	Beam angle
OLFA3040300WC3B10	3000 K	10°
OLFA3040300WC4B10	4000 K	10°
OLFA3040300WCRGBWB10	RGBW	10°
OLFA3040300WC3B20	3000 K	20°
OLFA3040300WC4B20	4000 K	20°
OLFA3040300WCRGBWB20	RGBW	20°
OLFA3040300WC3B30	3000 K	30°
OLFA3040300WC4B30	4000 K	30°
OLFA3040300WCRGBWB30	RGBW	30°
OLFA3040300WC3B45	3000 K	45°
OLFA3040300WC4B45	4000 K	45°
OLFA3040300WCRGBWB45	RGBW	45°
OLFA3040300WC3B60	3000 K	60°
OLFA3040300WC4B60	4000 K	60°
OLFA3040300WCRGBWB36	RGBW	60°

OLFA3040350W 350w options

Part Number	CCT	Beam angle
OLFA3040350WC3B10	3000 K	10°
OLFA3040350WC4B10	4000 K	10°
OLFA3040350WCRGBWB10	RGBW	10°
OLFA3040350WC3B20	3000 K	20°
OLFA3040350WC4B20	4000 K	20°
OLFA3040350WCRGBWB20	RGBW	20°
OLFA3040350WC3B30	3000 K	30°
OLFA3040350WC4B30	4000 K	30°
OLFA3040350WCRGBWB30	RGBW	30°
OLFA3040350WC3B45	3000 K	45°
OLFA3040350WC4B45	4000 K	45°
OLFA3040350WCRGBWB45	RGBW	45°
OLFA3040350WC3B60	3000 K	60°
OLFA3040350WC4B60	4000 K	60°
OLFA3040350WCRGBWB36	RGBW	60°