XL marlin Lighting

GARDEN Urban lighting

Model: OLPMA



General Data

Power	35W/60W/100W
LED type	Cree,Osram LED
Luminous flux	120 lm/W
ССТ	3000K or 4000K as standard. Different CCT upon request.
CRI	70/80
Beam angle	90°/ Asymmetrical
Dimension	Ø450x135mm
Lamp Life	50000 hrs
SDCM	≤5
Body colour	Grey,Black
Oper. Temp.	-30 °C up to +50 °C
Certifications	CE, RoHS
Input voltage	AC 100-270V, 50/60Hz

Construction Data

IP rating	IP65 Waterproof
Installation Pipe	Ø60/76mm
Housing	Aluminum lamp body
Housing finish	Polyester powder coating
Optic	Polycarbonate
Impact resistance	IK 08
Protector	Tempered glass
Driver	Meanwell

Pole options (Black)

(DidCR)	
Part Number	Pole Length
OLP400B	4000mm
OLP500B	5000mm
OLP600B	6000mm

(Grey)

Part Number	Pole Length	
OLP400G	4000mm	
OLP500G	5000mm	
OLP600G	6000mm	

APPLICATIONS

Simple appearance, easy to integrate with theenvironment. Specially designed for squares, parks and gardens areas.

PRODUCT DESCRIPTION

Reinforced die-casting body and reflector, smooth self-cleaning surface, nice appearance design And strong structure design. High efficient integrated heat radiation design, Electrostatic powder painting, high strength anti-corrosion, long lifespan. Plug type waterproof design, Waterproof more durable and effectively, Up to IP65.

FIXTURE CONSTRUCTION

Aluminium lamp body; Polycarbonate Optic, Polyester powder coating Housing finish with Tempered glass Protector, Meanwell Driver band and IP65

Symeterical Beam angle

Lamp	options	(RIACK)

Part Number	Watts	CCT
OLPMAS35WC3B	35W	3000K
OLPMAS35WC4B	35W	4000K
OLPMAS60WC3B	60W	3000K
OLPMAS60WC4B	60W	4000K
OLPMAS100WC3B	100W	3000K
OLPMAS100WC4B	100W	4000K

Lamp options (Grey)

Part Number	Watts	CCT
OLPMAS35WC3G	35W	3000K
OLPMAS35WC4G	35W	4000K
OLPMAS60WC3G	60W	3000K
OLPMAS60WC4G	60W	4000K
OLPMAS100WC3G	100W	3000K
OLPMAS100WC4G	100W	4000K

Asymmetrical Beam angle


Lamp options (Black)

Watts	CCT
35W	3000K
35W	4000K
60W	3000K
60W	4000K
100W	3000K
100W	4000K
	35W 35W 60W 60W

Lamp options (Grey)

Part Number	Watts	CCT
OLPMAA35WC3SG	35W	3000K
OLPMAA35WC4SG	35W	4000K
OLPMAA60WC3SG	60W	3000K
OLPMAA60WC4SG	60W	4000K
OLPMAA100WC3SG	100W	3000K
OLPMAA100WC4SG	100W	4000K

POLE Length



Photometric Data

