

Model: MY12 Modular



General Data

Power	12 W
LED type	CREE LED
Luminous flux	1100lm
CCT	3000K or 4000K as standard. Different CCT upon request.
CRI	80+
Beam angle	12° / 24° / 36°
Dimension	Ø50x91mm
Cut out dia.	-
Weight (kgs)	0.90 Kgs
Lamp Life	50000 hrs
SDCM	≤5
Oper. Temp.	C -10° +45°
Certifications	CE, RoHS
Trim Color	Black
Dimming	1-10V/DALI

Construction Data

IP rating	20 Indoor
Housing	Solid aluminum housing CNC machined body
Protection finishing	passivated (anodizing) anti-corrosion finishing
Glass	Tempered glass diffuser
Loading capacity	/
Cable Gland	IP20
Gasket	Silicone rubber gasket

Electrical Data

Input voltage	AC 220V 50/60hz
Cable	Cable gland

Accessories

Mounted Accessory	/
Clip	/

APPLICATIONS

High output LED 12W LEDlamp with driver, can be used with wide range of trims to suite different applications and lighting solutions.


PRODUCT DESCRIPTION

Modular high out put 12W LED lamp attached to aluminum heat sink and remote driver, suitable to use with our Modular down light range, comes with 300 K, 4000K color tempretures, and 40° beam angleswith excellent color rendering 80 Ra. optional dimming1-10 V or Dali on request

FIXTURE CONSTRUCTION

Aluminum reflector, and die cast aluminum heat sink and electronic driver.

Dimension Drawing



Lamp Options

Part Number	CCT	Beam angle
MY12312	3000 K	12°
MY12412	4000 K	12°
MY12324	3000 K	24°
MY12424	4000 K	24°
MY12336	3000 K	36°
MY12436	4000 K	36°

Photometric Data

